

EXPONA Design Flooring

EXPONA
COMMERCIAL

Supplier

Roller adhesives / Dry adhesives

EXPONA
DESIGN

ARDEX GmbH

AF 185

EXPONA
DOMESTICBOTAMENT
Systembaustoffe GmbH & Co. KG

BOTAMENT K 572

EXPONA
LIVING

G.A. Kiesel GmbH

Okatmos RF 220

Sika Deutschland GmbH

iFLOOR

PCI Augsburg GmbH

DT 100
DT 200

Uzin Utz AG

U 3000

Uzin Utz AG

SWITCHTEC
Sigan 1, 2 *
Sigan Elements
Sigan Elements Plus

Wakol GmbH

D 3330

* The suitable subsurfaces from Sigan 1 and 2 can be found at www.uzin-utz.com.

EXPONA design floor coverings must be air conditioned for at least 48 hours on site and they must be carefully rolled or rubbed down after being laid.

Roller adhesives and dry adhesives allow greater change in floor covering dimensions.

All the adhesives that we recommend must be used in accordance with the respective manufacturer's specifications.

Any adhesives that are not listed in this recommended list have not been tested. They have not been tested for compatibility with our products.

Note:
A thermosetting resin adhesive must be used when installing design floor coverings in conservatories or rooms with large banks of windows with a high level of solar radiation.